

Technical data RR 18.16 C + flange ø 28 mm code 23778

Description

3-piston alternating volumetric pumps for use on cleaning units and industrial systems. Hollow shaft pump with included flange for electric motor B14 100 - 112 IEC34-7, 4 poles 50 Hz.

Pump body and cover in die-cast aluminium alloy.

Side cover incorporate oil sight glass.

Rear cover with oil drain outlet. Oil level on body pump.

Pistons driven by crank-connecting rod mechanism.

Pump shaft in pressed high-strength steel.

Oversized friction bearings.

Connecting rods in die-cast special low-friction zinc-aluminium alloy.

One-piece ceramic pistons.

Pump head in pressed brass.

Double gasket sealing system.

Intake and delivery valves have plugs for easier maintenance.



| Details | Value |
|-----------------|-----------------------------|
| Category | Cleaning |
| Series | 322 - RR, RRA, RRV |
| Pump type | RR 18.16 C + flange ø 28 mm |
| Versioning | C |
| ARCode | 23778 |
| Output (lt/min) | 18 |
| Output (gpm) | 4.75 |
| Pressure (bar) | 160 |
| Pressure (psi) | 2300 |
| Power (hp) | 7.5 |
| Power (kw) | 5,5 |
| RPM | 1450 |
| Weight (kg) | 8 |

